**CNC-Attachments** 



## Economical tapping attachments with modular straight shank

The SPD CNC are low cost, self-reversing tapping attachments for CNC machining centers. They use ER collets and employ a simple stop arm system for easy installation on machines with automatic tool change.

The SPD CNC were developed specifically for short run job shop applications. Their low cost make them economical to use, and they provide all the advantages associated with the elimination of machine spindle reversal. Faster cycle time, elimination of machine spindle wear and tear due to reversal, lower energy costs and longer tap life.





## Features and Advantages

- ☐ faster cycle time
- eliminates machine reversal for lower energy costs and reduced wear to machine spindle
- □ ER collets
- simple installation with torque bar and stop arm
- 🛛 Stop Arm Assembly included
- □ simple programming

## How to Order

Please select the Tapping attachment (A) and CAT, SK or BT shank (C) to fit your machine. Please order accessories like collets, and torque bars separately. Please note the tool comes with a stop arm that can be modified or you can also order a readymade stop arm to fit your machine's bolt circle. Torque bar holders are not included and need to be ordered according to the bolt size of your machine.



## (A) Tapping Attachment SPD CNC Cylindrical Shank

| Model    | Order code              | Shank       | Capacity<br>(steel)  | Collets | Max. RPM | Weight kg | d  | L1  | L2 |
|----------|-------------------------|-------------|----------------------|---------|----------|-----------|----|-----|----|
| SPD CNC3 | 0283251152<br>028311152 | 25 mm<br>1″ | M2-M6<br>#4-1/4″     | ER11    | 2000     | 1.7       | 19 | 106 | 73 |
| SPD CNC5 | 0285251652<br>028511652 | 25 mm<br>1″ | M4.5-M12<br>#10-1/2" | ER16    | 1500     | 3.7       | 28 | 140 | 91 |

Notes: The SPD CNC tools include a stop arm assembly, but it is possible to use the RDT25 and 50 stop arm assemblies with them as well. When using Roll Form Taps the tool's capacity must be reduced 25 %. All dimensions are shown in mm. 25.4 mm = 1



| Order code | Center dista |  |  |  |
|------------|--------------|--|--|--|
|            | mm           |  |  |  |
| 723420     | 53-69        |  |  |  |
| 723421     | 68-77        |  |  |  |
| 723422     | 74-88        |  |  |  |



**Torque Bar Holder Assemblies** Page 55

Pages 55-57

Page 49

Steel Collets

Stop Arm Plate

723423





86-100



Cover

nce

Pages 52-54

Speed Chart

Installation

Programming

Interchangeable

Steep Taper

(C)